

CONNECTING DEVICES

M123-



Type:

**CLAMPS CONNECTION DEVICE
SOCKET + PLUG WITH 3
OR 5 POLES**

Rated voltage:

400 V

Rated current:

32 A

Working temperature:

T 125°C

Type of clamps to
connect the cables:

SCREW CLAMPS

Clamps connecting capacity:

1,50 ÷ 4,00 mm²

Protection degree (IP):

IP00

In conformity to the standards:

EN 61984

In conformity to the requirements
of the directive:

2014/35/EU

Approval marks:

IMQ



- Connection device socket + plug with 3 or 5 poles:
 - envelopes, plug in black PA66 and socket in red PA66 or grey or transparent polycarbonate, diameter 16 mm for the version with 3 poles, diameter 22 mm for the version with 5 poles.
 - bush screw clamps, in nickel-plated brass, with slot screw in zinc-plated iron.

- Device suitable to connect the internal wiring of the lighting fixtures. Especially useful for applications in cylindrical housings such as tubes and staffs.

Note: check if during the use, the correct air distances of the parts under tension are respected.

- The clamp can be connected with cables arranged with stripping 6mm or crimped with end-terminal.

M123N/3: plug + socket with 3 poles in black PA66.

M123E/3: plug + socket with 3 poles in grey polycarbonate.

M123T/3: plug + socket with 3 poles in transparent polycarbonate.

M123N/5: plug + socket with 5 poles in black PA66.

M123E/5: plug + socket with 5 poles in grey polycarbonate.

M123T/5: plug + socket with 5 poles in transparent polycarbonate.

