

MULTI-CONDUCTOR CABLES INSULATED IN FEP + FEP T200°C cURus

XQ---

1997



Type of insulation:

**FEP + FEP UR
STYLE 21167**

Working temperature:

T 200°C

Type of conductor:

**NICKEL-PLATED COPPER
600 V**

Working voltage:

In conformity to the standard:

UL 758 AWM STYLE 21167

Approval marks:

cURus



PROCESSED WIRE FILE E221012

RESPOOLED WIRE FILE E221012

- AWG table of the cores:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
XQ28-	2 x 18	48 x 0,161	tn tb	P	flat	2,9 x 5,2
XQ38-	3 x 18	48 x 0,161	tn tb + ground	P	oval	4,7 x 5,9

- Other AWG on request.

* Table of the lines colours to identify the cores:
tn = black tb = white



* Cores position table:
P = parallel

XA--T: version with insulated 24 AWG steel self-supporting wire rope, with 35 kg breaking load.



- AWG and multiple table of the cores for the version with steel wire rope:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
XA28-	2 x 18	48 x 0,161	tn tb	P	oval	4,7 x 5,9
XA38-	3 x 18	48 x 0,161	tn tb + ground	P	oval	5,7 x 5,9



- UR approval printing, with white ink, on the sheath.





XQ28-



XQ38-



XA28-



XA38-

- Table of available colours:
T = transparent (sheath and cores)
N = black
B = white
- Other colours on request.

